

# DURASEAL



## PRODUCT DESCRIPTION

\*Duraseal is a free flowing liquid penetrating sealer for concrete surfaces.\*It is recommended for water repellency for Terrace floors, Chajjas, Vertical plasters\*It has good Penetration property in concrete After the initial application of Duraseal, it reacts with the atmospheric moisture or pore water in the substrate there by generating the active ingredient & liberating the alcohol. The reacted Duraseal greatly reduces the water absorbency of the substrate.

## PURPOSE:

DURASEAL is used as a Impregnating Non film forming type water repellent for rendering External Plaster, Vertical walls, Horizontal IPS floors & parapet walls. It is also recommended to be used as a Primer before applying any Exterior emulsion based acrylic paint or coating to increase the long term durability of the plaster surface

## APPLICATION GUIDELINES:

Area to be applied should be free from dust, grease etc

Remove the material in a clean & dry container.

Remove only the required quantity of the material that you can consume for the required area.

Do not mix the used & the unused material together.

Apply the material by a clean brush, let the material penetrate in to the surface.

Apply a 2<sup>nd</sup> coat immediately wet on wet within 30 minutes of applying the 1<sup>st</sup> coat.

## ADVANTAGES:

\*It's a Penetrating ,breathable UV resistant, water repellent sealer

\*It has good Penetration property it penetrates to about

\* 1.5 to 2.5mm deep in the plastered surfaces.

\*It is alkaline resistance

\*Tack free drying

\* Unaffected by UV radiation

\* Non film forming

\* Effective even on slightly damp surfaces.

\*Extremely fast water repellency development

\*can be easily applied by brush

\* Gives excellent long term water Repellency

\*Prevents the structural steel reinforcement from corrosion due to moisture penetration as it avoids the penetration of moisture from outside to inside, but at the same time as it is breathable in nature it allows the internal moisture to escape outside.

\* Performs as a Anticarbonation non film forming impregnating sealer

## PRODUCT SPECIFICATIONS:

Appearance	Free flowing clear liquid
Colour	Water clear
Method of application	By Brush or Airless spray
Coverage	50 to 60sqft/ltr/coat**
Recoating Interval	wet on wet within 30 minutes
Number of coats Recommended	2 on plaster & 3 on parapets
Fungus Resistance	Very Good
Shelf Life	1 year in a properly sealed drum

**STORAGE:**

Store in a cool & dry place away from sunlight & keep it properly closed after every use.

**PACKING:**

20 Ltr,35Ltr & 200 Ltr Drums

The information contained herein is believed to be accurate and is offered in good faith for the guidance of the consumer. We cannot accept any responsibility for errors in, or misinterpretation of the information contained in this brochure. In view of our constant endeavor to improve the quality of our products, we reserve the right to alter or change the specifications without prior notice

**For Details Contact :**

TEJ INNOVATIVE PRODUCTS B-4,P-10,ABOVE I.O.BANK,H.F.S.ROAD, JOGESHWARI(EAST) MUMBAI-400060 INDIA  
Tel. : (O):0091-22-28246536 / 22970165 Cell:0091-9821170321 / 9224284850 Email: tejas\_t@yahoo.com OR tejas60@gmail.com