



DURACON CONCRETE DENSIFIER (DCD-L)

PRODUCT DESCRIPTION:

Duracon Concrete Densifier (DCD-L) is liquid Surface Hardener & concrete densifier. It is a ready to use solution formulated to harden & densify concrete based (cementitious) surfaces

PURPOSE:

Used to densify & harden cementitious based Concrete surfaces, It penetrates the surface & reacts with the free lime present in the substrate to form a dense CSH gel which fills up the voids & pores of the concrete surface & thus densifies it.

USAGE:

It is a ready to use liquid solution which can be easily applied by a brush,,Roller,or a spray. It can also be diluted in ratio of 1:1 (DCD-L : Plain Clean Water) Don't use Hard water

ADVANTAGES:

- * Excellent as a Dust proofing agent in server rooms & Industrial Floorings
- * Penetrates deep into the surface to harden and decrease the porosity of the surface.
- * It improves the light reflectance and on polishing the surface results in permanent and attractive sheen.
- * It provides a tough protected surface that does not discolour or show pedestrian or vehicular wear marks.
- * Improves the abrasion resistance of the surface.
- * It improves the chemical resistance of the surface.
- * Protects the surface against scratching or peeling thus making it dustproof.
- * Treated surface is Breathable ,but seals the micro pore structure of concrete
- * Ready to use and can be easily applied.
- * will not yellow,discolour,chip.or fade like conventional floor sealers
- * Treated surface is UV stable & maintains the natural look of the concrete floor
- * It can be applied in both new as well as old constructions.
- * VOC content is nil, thus helps earning LEED points in green building earning.
- * It is economical to use.

Uses:

- * It is recommended for use wherever Hardened,Dustproof and improved chemical and abrasion resistant surfaces are required.
- * Ideal applications include floors of industrial plants and warehouses, storage silos, sewage plants,IT Server Rooms, chemical processing facilities, refineries, car parking and heavy pedestrian traffic areas such as malls, stadiums, hospitals, airports and public places.
- * Also, where aesthetics is required, on polishing the surface a light sheen is obtained.
- * It can be sprayed on concrete structures to improve the life of the structure.
- * It classifies as Green building product, as it is VOC compliant .

..... Cont

Application Guidelines:

* Clean the surface before application. If there is coating on the surface, for eg curing compound etc., it should be removed. Fill and repair all holes, cracks spalled & deteriorated surface areas with RMPM (refer relevant datasheet). For best result, the surface should be touch dry to allow the Liquid Densifier to penetrate the pores and react.

DCD-L is concentrated material and can be diluted with 1:1 parts of soft water for every one part of DCD-L

*. It can be applied on old or new clean surface by using a low-pressure sprayer, roller or brush.

*For Horizontal surfaces, apply enough diluted DCD-L to keep the surface wet for 20 minutes. If areas dry out before that, apply more diluted DCD-L.. In hot, dry or windy conditions dampen concrete before application to prevent flash drying.

*Remove any dried powder residue using a stiff broom, power sweeper or floor scrubbing machine. For immediate, enhanced shine, buff or burnish the dry concrete surface in both directions using an orbital floor machine or burnisher equipped with an appropriate polishing pad. It is generally a dry buffing operation.

*For vertical surfaces, apply from the bottom up. For maximum penetration and desired coverage rates, a wet-on-wet application is recommended; retreat within three to five minutes after initial application. Repeated applications should be made until the surface remains moist for a minute or so before solution disappears.

Precautions :

* Immediately wash off over-spray from glass, aluminum, or highly polished surfaces with water to avoid etching of surfaces. Failure to thoroughly wash and remove all excess material from floor surfaces may result in unsightly white stains

* Surfaces to receive the treatment should be preferably dry.

* Avoid & Restrict the usage of the treated surface for 12 hours.

*Avoid contact with eyes, skin and clothing. In case of skin contact, wash immediately. In case of eye contact, flush immediately with water for at least 15 minutes and obtain prompt medical attention

Product Properties

Specific Gravity at 25°C : 1.19 +/- 0.02

pH : Alkaline

Application temperature

Coverage

Shelf Life:

VOC Content : Nil

Minimum 10 to 15 Deg Cent

1st Coat :75 to 80sft 2nd Coat :90 to 120sft**

1 Year if stored in a sealed container

Packing:

60 / 200 Kg

**Depending on the porosity and the type of substrate

Disclaimer

The information contained herein is believed to be accurate and is offered in good faith for the guidance of the consumer. We cannot accept any responsibility for errors in, or misinterpretation of the information contained in this brochure.

In view of our constant endeavor to improve the quality of our products, we reserve the right to alter or change The specifications without prior notice

For Details Contact :

TEJ INNOVATIVE PRODUCTS B-4,P-10,ABOVE I.O.BANK,H.F.S.ROAD, JOGESHWARI(EAST) MUMBAI-400060 INDIA

Tel. : (O):0091-22-28246536 / 22970165 Cell:0091-9821170321 / 9224284850 Email: tejas_t@yahoo.com OR tejas60@gmail.com